

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A three-dimensional textured stair tread cover comprising:

a first portion having a first surface, a second surface, and at least one side wall extending between said first and said second surfaces; and

a second portion having a first surface positioned at a substantially permanent angle relative to said first surface of said first portion, a second surface, and at least one side wall extending between said first and said second surfaces of said second portion,

wherein said angle between said first surface of said first portion and said first surface of said second portion is at least 45 degrees; and said first portion and said second portion are integral and comprise a web and a binder, said web comprising a multitude of substantially continuous three-dimensionally undulated thermoplastic filaments autogenously bonded where they contact one another, wherein said filaments have a diameter in a range from 0.1 to 3 mm and said web has a thickness of at least 0.5 cm and a coil weight in a range from 0.1 to 3.0 kg/m²,

wherein the first portion forms an anti-slip surface for foot traffic, and wherein the second portion is configured to extend along the front of a step when the three-dimensional textured stair tread cover is placed on a step.

2. (previously presented) The textured stair tread cover of claim 1 wherein said thermoplastic filaments comprise a polyamide.

3. (previously presented) The textured stair tread cover of claim 1 wherein said thermoplastic filaments comprise at least one of polycaprolactam or poly(hexamethylene adipamide).

4. (previously presented) The textured stair tread cover of claim 1 further comprising a quantity of particles affixed to at least one of said first or said second surface of said first portion.

5. (previously presented) The textured stair tread cover of claim 4 wherein said quantity of particles is in a range from 0.1 to 5 kg/m².

6. (previously presented) The textured stair tread cover of claim 5 wherein said quantity of particles comprises at least one of slag, alumina, thermoplastic polymer, thermoset polymer, glass, mullite, sand, rubber, pumice, topaz, garnet, corundum, silicon carbide, zirconia, ceramic aluminum oxide, or diamond.

7. (previously presented) The textured stair tread cover of claim 1 wherein said binder comprises polyurethane.

8. (previously presented) The textured stair tread cover of claim 1 further comprising a size coat.

9. (previously presented) The textured stair tread cover of claim 8 wherein said size coat comprises polyurethane.

10. (previously presented) The textured stair tread cover of claim 8 wherein said size coat further comprises yellow colorant.

11. (previously presented) The textured stair tread cover of claim 8 further comprising a graphic on said first surface of said first portion.

12. (previously presented) The textured stair tread cover of claim 1 further comprising a third portion integral with at least one of said first or said second portion, said third portion comprising a first surface, a second surface, and at least one side wall extending between said first and said second surfaces of said third portion.

13. (previously presented) The textured stair tread cover of claim 12 wherein said third portion is integral with said second portion, and said first surface of said third portion is positioned at an angle of at least 45 degrees relative to said first surface of said second portion.

14. (previously presented) The textured stair tread cover of claim 1 wherein said first and second portions are each substantially planar.

15. (currently amended) The textured stair tread cover of claim 1 wherein said sidewall extending between said first and second surfaces of said first portion is ~~in a range from 0.5 cm up~~ to 8 cm high.

16. (canceled)

17. (previously presented) A stairway comprising a plurality of steps, wherein at least one step comprises the textured stair tread cover of claim 1.

18. (previously presented) A ladder rung comprising the textured stair tread cover of claim 1.

19. (withdrawn – currently amended) A method for making a three-dimensional textured stair tread cover comprising:

providing a nonwoven sheet comprising a web and a binder, said web comprising a multitude of substantially continuous three-dimensionally undulated thermoplastic filaments autogenously bonded where they contact one another, wherein said filaments have a diameter in a range from 0.1 to 3 mm and said nonwoven sheet has a thickness of at least 0.5 cm and a coil weight in a range from 0.1 to 3.0 kg/m²;

heating at least a portion of said nonwoven sheet;

positioning a first portion of said nonwoven sheet at an angle relative to a second portion of said nonwoven sheet; and

cooling said nonwoven sheet to form a substantially permanent angle of at least 45 degrees between a first surface of said first portion and a first surface of said second portion,

wherein the first portion forms an anti-slip surface for foot traffic, and wherein the second portion is configured to extend along the front of a step when the three-dimensional textured stair tread cover is placed on a step.

20. (withdrawn) The method of claim 19 further comprising:

providing an outer forming tray comprising a first forming surface and a second forming surface positioned at an angle relative to said first forming surface; and

placing at least a portion of said nonwoven sheet in said outer forming tray such that said first portion of said nonwoven sheet contacts said first forming surface and said second portion of said nonwoven sheet contacts said second forming surface.

21. (withdrawn) The method of claim 20 further comprising cooling said nonwoven sheet in said forming tray.

22. (withdrawn) The method of claim 20 further comprising placing an inner forming tray in at least a portion of said outer forming tray such that at least one of said first portion or said second portion of said nonwoven sheet simultaneously contacts said inner and said outer forming trays.

23. (withdrawn) The method of claim 19 wherein said heating occurs in an oven set at a temperature in a range from 190 to 205 degrees Celsius.

24. (withdrawn) The method of claim 19 wherein said thermoplastic filaments comprise a polyamide.

25. (withdrawn) The method of claim 19 further comprising printing said nonwoven sheet.

26. (withdrawn) The method of claim 19 wherein said nonwoven sheet further comprises a quantity of particles.